

**POWEROIL WHITE OIL - 22****(TECHNICAL GRADE WHITE OIL)**

Meets requirements of US FDA 21 CFR 178 . 3620 (b) Standard.

Sr. No.	Characteristics	Unit	Test Method	Typical Data	
				Min	Max
1.	Appearance		Visual	Transparent, colourless , bright and clear oily liquid.	
2.	Colour	Saybolt	ASTM D 156	+ 25	
3.	Density at 25 °C	gms / ml	ASTM D1298	0.82	0.85
4.	Kinematic viscosity at 40 °C	cSt	ASTM D445	19.8	24.2
5.	Flash Point , (COC)	° C	ASTM D 92	170	-
6.	Pour Point	° C	ASTM D 97	-	-12
7.	Ultraviolet Absorbance, 280 to 289 nm 290 to 299 nm 300 to 329 nm 330 to 350 nm	Abs / cm	CFR 178.3620 (b)	- - - -	4.0 3.3 2.3 0.8

POWEROIL White Oil 22 is a light white oil formulated from highly refined hydrotreated base oils which is colourless , tasteless and odorless. It meets requirements of US FDA 21 CFR 178.3620 (b).

Application : POWEROIL White Oils are suitable for use in process requiring clear white oils. They find extensive usage in textile processing (non staining lubrication) , incense & perfume manufacture , plastic , paper and cosmetic industries , several oil based formulations , hair oils , hair lotions , shoe polish and petroleum jelly manufacturing industries.

Performance Benefits : Excellent oxidation resistant
High film strength
Non staining

(Version # 5 1st October , 2009)