



### POWER PRESS 32, 46 & 68 COMPRESSOR OILS

**POWER PRESS OILS** are best in class mineral oil based air compressor oils designed to meet the stringent performance requirements of the compressor manufacturers. Power press oils are formulated from high quality carefully chosen solvent refined base stocks with superior performance additive package to deliver top of the line performance coupled with excellent equipment protection.

**PERFORMANCE STANDARDS:** ISO DIS-6521  
DIN 51506VD-L  
BIS -13256-1992

CHARACTERISTICS	POWER PRESS		
	32	46	68
ISO VG	32	46	68
Colour	2.0	2.5	2.5
Kinematic Viscosity @ 40°C, cSt	29 - 35	41 - 51	61 - 75
Viscosity index, min	95	95	95
Flash point, COC, °C, min	196	200	204
Pour point, °C, max	-9	-9	-9
CCR % Wt. (typical)	0.05	0.05	0.05
Rust test D-665 (A&B) 24 hrs	Pass	Pass	Pass

#### APPLICATION:

- Recommended for lubrication of severe duty reciprocating and rotary air compressors with air discharge temperature upto 220°C.
- Suitable for lubrication of most types of OEM equipments e.g. Atlas copco, Ingersoll – Rand etc. as product meets OEM performance requirement provided viscosity grade as recommended by OEM is selected from the range.

#### PERFORMANCE BENEFITS:

- Good lubrication even under high operating temperature
- Excellent corrosion and rust protection characteristics
- Excellent anti wear properties offering enhanced equipment life
- Reduced fire and explosion risks due to low volatility and high auto ignition temperature
- Low carbon and deposit forming characteristics

(Version # 1 April 14<sup>th</sup> 2008)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.